

# Pytes

## V15



## Features

---




### Safe

LFP Chemistry, Tier 1 Automotive Cells & Field-Proven BMS



### Smart

Remote Upgrading & Monitoring



### Widely Compatible

Compatible with 20+ Inverters



### Powerful

7.17kW Powerful Output,  
14.34kWh High Capacity



### Elegant

Sleek and Minimalist Design with Clean Lines, Featuring Hidden Interface



### Easy To Install

Wheelable & Less Wiring  
One Battery for the Whole Family

# V15 Specifications



## Electrical

Nominal Voltage	51.2V
Nominal Capacity	280Ah
Nominal Energy	14.34kWh
Recommended Charge/ Discharge Current	140A (7.17kW)
Maximum Charge/ Discharge Current	200A (10.24kW))
Peak Discharge Current	300A(15.36kW@15s)

## General

Chemistry	LFP
Communication Protocol	RS485/CAN/Dry Contact/Wifi
Dimensions (W*D*H)	27.56*11.10*28.74inch/ 700*282*730mm
Weight	297.62 lbs/135KG
Operating Temperature	Charge: 32~131 F/0~55 C Discharge: -4~131 F/-20~55 C
Cycle Life	6000 cycles
Ingress Protection Code	IP21
Altitude	< 13123.35ft ( 4000m )
Warranty	10 Years

## Inverters Compatibility List

### Main Inverter Partner



**Pytes**

PYTES (USA) ENERGY, INC

Address: 13921 Senlac Dr, Farmers Branch, TX 75234  
 Site: [www.pytesusa.com](http://www.pytesusa.com)  
 Email: [pytesusa@pytesgroup.com](mailto:pytesusa@pytesgroup.com)



LinkedIn



Facebook



YouTube



[www.pytesusa.com](http://www.pytesusa.com)

Pytes